

Scissor Lift

Used Scissor Lift Washington - The industrial equipment that utilizes crisscrossed steel linked arms is scissor lifts. Scissor lifts create an “X” support network to facilitate vertical lifting. Workers use a sizeable rectangle platform that is secured to the top of the lifting apparatus. There are secure support railings along the platform edge for extra safety and to keep the operator safe. The scissor lift showcases a low profile that is excellent for compact, hard surfaces including pavement and concrete. Scissor lifts can use an electric motor or a combustion engine to transport and lift the machine. Since the scissor lift functions on a vertical plane, if it needs to be repositioned horizontally, the operator will have to move it into place. The lifting components of both regular lift models and rough terrain units rely on the same lifting technology. The rough terrain is specially designed for traversing uneven ground. These machines rely on large all-terrain tires to allow rough terrain scissor lifts to traverse difficult locations while offering higher ground clearance. These scissor lifts feature 4WD to get through muddy and difficult terrain. Lower lifting heights are offered due to the higher center of gravity. If you have never operated one before, scissor lifts can seem strange or intimidating. Even though images of scissor lifts moving with the wind are easy to imagine, know that they have been specifically designed to provide complete operator safety and you won't even feel the unit moving as it ascends or while it is extended. A variety of safety tests have to be completed before this unit can be sold. Of course, if you are new to this kind of equipment, it is normal to feel unsure until you familiarize yourself with the unit. Maintain safety procedures at all times. Understanding what you will be using your scissor lift for will help ensure you have the right type of model. The unit you need will vastly depend on the kind of work you need to do. How high you need to travel and how heavy the loads you will be transporting are all key factors. There are different models on the market that can help you reach various heights. Compact units are often used for interior locations including factories, warehouses or freight locations. If you do not need the highest capacity model, there is no need to choose the largest unit available. Optional railings and platforms are available on electrical scissor lifts to provide maximum safety. These machines are designed to be reliable and safe. Many safety inspections and specifications need to be maintained in order for these industrial machines to be available for sale. Scissor lifts enable us to finish tasks that normally are inaccessible or unreachable otherwise. These lifts elevate vertically; therefore, the machine is parked in place prior to lifting. Before the lift is engaged, the operator will properly position the unit. Numerous safety features have been designed into the machine. Safety is accomplished by following operational guidelines. There is a safe basket workspace on scissor lifts to ensure lifting tasks are more secure as opposed to hanging off of scaffolding or a ladder. Most scissor lifts utilize internally mounted batteries located inside the base of the machine to provide power. Charging is required after a long sitting for an extended time or working a long shift. Batteries may be changed every 12 hours or charged many times throughout the day. To facilitate scissor lift charging, the operator can park the machine close to an electrical outlet in a well-ventilated place. The emergency shut-off switch is engaged upon parking to prevent other operators from driving off while plugged in. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. The battery charger is commonly located on the right side of the lift on the base. Many older models may feature the battery charger mounted on the back of the scissor lift. The charger for the machine is plugged into the AC extension cord within a well-ventilated area and the extension cord plugs into an electrical outlet. The electrical cord length on the battery charger has to be short for safety reasons to prevent the unit from running over it. There is a high possibility for extreme danger if excess extension cord length dropped out of the battery charger storage area during operation. After the scissor lift plugs in to charge, all of the lights should become lit up. Once the unit is plugged in, the batteries automatically start to charge. After the charging is complete, the battery lights switch to green and the charger shuts down. Models that are older and rely on a meter will show zero volts after they are charged

fully and then the charger will also turn off automatically. After the scissor lift is completely charged, the unit is ready to get back to work. It is common for warehouses and businesses to have numerous batteries continually charging to keep the scissor lift operating 24 hours a day.